

Label Rewinder, (RW4S, RW6S & RW4L, RW6L)



Picture shows RW4S for Intermec PX4i, PX5i Printer
Can be ordered to fit any Printer models

Rugged external rewriter for labels, tickets and tags.

The Rewinder is designed for rewinding the printed labels as they come out of the printer. The method of rewinding labels externally offers advantages in case you want to apply the labels manually or automatically later on.

The Rewinder can match the printer maximum speed and takes the whole label roll that contained in the printer.

Rewinding is done neatly and efficiently. Besides, it is a silent operation.

You can control rewinding direction and power on/off.

As the inner diameter of the paper bobbin often varies, an adjusting plate on the bobbin shaft will suit bobbins having diameter of 38 - 42 mm.

When no paper bobbin is used, the label web can be folded and fixed under the adjusting plate. No need for tape. Or use the U-guide to hold the web. Using the U-guide will make it easier to take off the label roll afterwards.

The Rewinder can be loaded with 3 inch bobbin without removing the adjusting plate.

- External Rewinding offers advantages for later application by hand or automatically labeling by a dispenser unit.
- Adapted for **Intermec and Sato Printers. (Can be suited to fit any Printer).**
- Rewinder matches printer's maximum speed.
- Available for 3" bobbin.
- Easy to control the Rewinder direction.
- Easy installation.



Picture shows RW4L Base model
Can be ordered to fit any Printer models

Label Rewinder, (RW4S, RW6S & RW4L, RW6L)

Product Name: Rewinder RW4S
Product Description: Universal Rewinder Unit
Article no: 108-00-03(or specific Art. Nr. For adaption to a specific Printer)

Technical Specs:

Label Width (max):	135mm	Power:	12V DC, 1A
Label Roll Size (max):	210mm	Switch:	On/Off
Unit Length (max):	250mm	Direction:	Yes/By Strap
Unit Width (max):	230mm	Start/Stop:	By Tension Arm and Photocell
Unit Height (max):	220mm		

Product Name: Rewinder RW6S
Product Description: Universal Rewinder Unit
Article no: 108-06-03(or specific Art. Nr. For adaption to a specific Printer)

Technical Specs:

Label Width (max):	180mm	Power:	12V DC, 1A
Label Roll Size (max):	210mm	Switch:	On/Off
Unit Length (max):	250mm	Direction:	Yes/By Strap
Unit Width (max):	230mm	Start/Stop:	By Tension Arm and Photocell
Unit Height (max):	220mm		

Product Name: Rewinder RW4L
Product Description: Universal Rewinder Unit
Article no: 108-00-04(or specific Art. Nr. For adaption to a specific Printer)

Technical Specs:

Label Width (max):	135mm	Power:	24V DC, 1,5A
Label Roll Size (max):	360mm	Switch:	On/Off
Unit Length (max):	250mm	Direction:	Yes/By Strap
Unit Width (max):	280mm	Start/Stop:	By Tension Arm and Photocell
Unit Height (max):	380mm		

Product Name: Rewinder RW6L
Product Description: Universal Rewinder Unit
Article no: 108-06-04(or specific Art. Nr. For adaption to a specific Printer)

Technical Specs:

Label Width (max):	180mm	Power:	24V DC, 1,5A
Label Roll Size (max):	360mm	Switch:	On/Off
Unit Length (max):	250mm	Direction:	Yes/By Strap
Unit Width (max):	280mm	Start/Stop:	By Tension Arm and Photocell
Unit Height (max):	380mm		



Wichrowa 49
 42 280 Czesochowa
 Poland

Phone: +48 34 366 63 08
 e-mail: info@nasab.com
 Internet: www.nasab.com